REFERENCES

[1] A.W.Smeulders,M.Worring,S.Santini, A.Gupta ,and R.Jain, "Content based image retrieval at the end of the early years," IEEE Ttrans.Pattern.Anal.Mach.Intell.,vol.223,pp.1349-1380,2000.

[2] T.Ojala,M.Pietikainen,and D.Harwood, "A comparative study of texture measures with classification based on featured distributions," Pattern Recognition, vol.29,pp.51-59,1996

[3] T.Ojala,M.Pietikainen,and T.Maenpaa, " Multiresolution gray-scale and rotation invariant texture classification with local binary patterns," IEEE Trans.Pattern Anal.Mach.Intell.,vol.24,pp.971-987,2002.

[4] Z.Guo,L.Zhang, and D.Zhang, " Rotation invariant texture classification using LBP variance with global matching," Pattern Recognition, vol.43,pp.706-719,2010.

[5] X.Qian,X.S.Hua,P.Chen,and L.Ke, "PLBP: an effective local binary patterns texture descriptor with pyramid representation," Pattern Recongnition, vol.44,pp.2502-2515,2011.

[6] S.A.Orjuela Vargaa,J.P.Yanez Puentes, and W. Philips, Local binary patterns: New variants and applications, vol.506, pp.85-112, DOI: 10.1007/978-3-642-39289-4_4.

[7] M.Subrahmanyam,R.P.Maheswari,andR.Balasubramanian,"Directional binary wavelet patterns for biomedical image indexing and retrieval," Journal of Med.syst, vol.36,pp.2865-2879,2012.

[8] M.Subrahmanyam,R.P.Maheswari,andR.Balasubramanian,"Local maximum edge binary patterns: a new descriptor for image retrieval and obejcet tracking," Signal processing(Elseiver),vol.92,pp.1467-1479,2012.

[9] M.Subrahmanyam,R.P.Maheswari,andR.Balasubramanian, "Local tetra patterns: a new feature descriptor for content based image retrieval,"IEEE Trans.Image Process.,vol.21,pp.2874-2886,2012.

[10] M.Subrahmanyam,Q.J.Wu, "Spherical symmetric 3D local ternary patterns for natural,texture and biomedical image indexing and retrieval," Journal of Neuro computing, vol.149,pp.1502-1514,2015.

[11] M.Subrahmanyam,Q.J.Wu, "Local Ternary Co-occurrence Patterns: A New Feature Descriptor for MRI and CT Image Retrieval," Journal of Neuro computing(Elsevier),vol.119,pp.399-412,2013.

[12] Subrahmanyam. Murala, QM.J. Wu, R.P. Maheshwari, and R. Balasubramanian, "Modified color motif co-occurrence matrix for image indexing and retrieval," Comput. Electr.Eng,vol.39,pp.762-774,2013.

[13] M. Verma, B. Raman, "Center symmetric local binary co-occurrence pattern for texture, face and bio-medical image retrieval," J. Vis. Commun. Image Represent,vol.32,pp.224-236,2015.

[14] Anu Bala, Tajinder Kaur, "Local Texton XOR patterns: A new feature descriptor for content-based image retrieval," Engineering Science and Technology, an International Journal,vol.19,March,2016

[15] Jie Chen, Shingian Shan,Guoying Zhao, and Xilin Chen, "A Robust Desriptor based on Weber's Law," IEEE Transactions on pattern analysis and machine intelligence, vol.32,pp.1705-1720,2009.

[16] Manisha Verma, Balasubramanian Raman,"Local tri-directional patterns: A new texture feature descriptor for image retrieval", Digital signal processing, vol.51, pp. 62–72, April 2016.

[17] M. Heikkilä, M. Pietikäinen, and C. Schmid, "Description of interest regions with center-symmetric local binary patterns," in: Computer vision, Graphics and image processing, pp.58-69,2006.

[18] L. Nanni, A. Lumini, and S. Brahnam, "Local binary patterns variants as texture descriptors for medical image analysis," Artif. Intell. Med., vol.49, pp.117–125,2010.

[19] S. Murala, Q.M. Wu, "Peak valley edge patterns: anew descriptor for biomedical image indexing and retrieval," IEEE Conference on Computer Vision and Pattern Recognition Workshops, CVPRW, pp.444–449, 2013.

[20] AT&T Laboratories Cambridge, the AT&T database of faces, available [Online] available: http://www.uk.research.att.com/facedatabase.html, 2002.

[21] Corel1kDatabase,[online] http://wang.ist.psu.edu/docs/related/.

[22] Brodatz texture database, [online]http://multibandtexture.recherche.usherbrooke.ca/original_brodatz.html.